

New From
Valcom!



Custom
Logos
Available



Digital Clocks

- Easy to Read
- Date & Time View
- 12 or 24 hour format
- Brightness Adjustments

| | |
|--|----------|
| 2.5" 24Vdc Digital Clock | V-D2425 |
| 2.5" 110Vac/24Vdc Digital Clock | V-D11025 |
| Surface (wall) Mount Housing | V-SM25 |
| Flush Mount Housing | V-FM25 |
| Double Mount Bracket | V-DM25-4 |
| 2.5" Digital Clock/8" Speaker Baffle | V-CSB25 |
| Surface Mount Backbox for VCSB25 | V-CSBF |
| Recessed Mount Backbox for VCSB25 | V-CSBRB |
| 4.0" 24Vdc Digital Clock | V-D2440 |
| 4.0" 110Vac/24Vdc Digital Clock | V-D11040 |
| Surface (wall) Mount Housing | V-SM40 |
| Flush Mount Housing | V-FM40 |
| Double Mount Bracket | V-DM40-4 |
| Chronograph Timer Control Box (for V-D11040) | V-CDT |
| 4" Wire Guard for use with 2.5" and 4.0" Digital Clocks | V-WGD4 |
| 6 Amp 2 Wire Clock Driver for use with 2.5" and 4.0" Digital Clocks (Optional) (Drives forty (40) 2.5" Digital Clocks or thirty (30) 4.0" Digital Clocks) | V-VCU |

Now use the same cable for Speaker, Call-in Switch, and Clock!

Cost effective, precision time clocks for schools, healthcare, universities, manufacturing, corporate and government. Valcom's synchronized clocks provide the single, facility wide time standard that is so important in managing an organization's daily schedule. Valcom's clocks offer innovative 2-wire correction which provides instantaneous time corrections following power outages and daylight saving time. The low energy circuit design permits using inexpensive Category 3/5/6 cable! Perfect for new installs, perfect for retrofits!

- Low Energy Circuits
- U.L. Approved Current Limited Power
- May be used with other master clock systems
- Self Learning Correction
 - Sync wire (58th, 59th minute, 3 wire)
 - Digital (2 wire correction)

*Reduce Installation
Time and Cost by 50%!*

Analog Clocks

- Metal Case
- Low Profile
- Built In Self Diagnostics
- Shatter Proof

| | |
|--|-----------|
| 12" Round, black, surface mount, 24Vdc | V-A2412 |
| 12" Round, black, surface mount, 110Vac | V-A11012 |
| Surface Mount Ring | V-SMR12 |
| Double Mount Bracket | V-BDM12-4 |
| Universal Mounting Bracket | V-UML |
| 12" Wire Guard | V-WGA12 |
| 16" Round, black, surface mount, 24Vdc | V-A2416 |
| 16" Round, black, surface mount, 110Vac | V-A11016 |
| Surface Mount Ring | V-SMR16 |
| Double Mount Bracket | V-BDM16-4 |
| 16" Wire Guard | V-WGA16 |
| 12" Analog Clock / 8" Speaker Baffle | V-CSB12S |
| Surface Mount Backbox for V-CSB12S | V-CSFB |
| Recessed Mount Backbox for V-CSB12S | V-CSBRB |
| 6 Amp 2 Wire Clock Driver for use with 12" and 16" Analog Clocks (Optional) (Drives 120 Analog Clocks) | V-VCU |

VALCOM

5614 Hollins Road • Roanoke, VA 24019
Ph: 800.825.2661 • Fax: 540.362.9800
www.valcomclocks.com